


*Our High Performance lead blocks with sheave size 32 and 45 are now also available with plan bearing sheaves instead of the standard aluminium ball bearing sheaves. The blocks have rivets in both ends and are bolted together with allen screws for easy disassembling if needed. The design is the same as known from our existing High Performance Series - the only difference is the sheave.*

*The lead blocks are supplied in standard polishing or high polished stainless steel.*



No. 011001 /011036

**Block features:**

**Block side in 2 mm stainless steel 316**

**Fasteners included**

**Plan bearing sheave in black delrin**

**Top/end in black delrin**

Article No.	Type	SWL kg (each sheave)	BL kg	Sheaves	Sheave size mm	Max rope mm	Length mm	Width mm	Height mm	Fasteners mm	Weight g
011000	Lead block 2 sheaved	500	1000	2	32 x 16	14	134	35	22	6	
011001	Lead block 3 sheaved	500	1000	3	32 x 16	14	176	35	22	6	
011002	Lead block 4 sheaved	500	1000	4	32 x 16	14	218	35	22	6	
011003	Lead block 5 sheaved	500	1000	5	32 x 16	14	260	35	22	6	
011004	Lead block 6 sheaved	500	1000	6	32 x 16	14	302	35	22	6	
011035	Lead block 2 sheaved	600	1200	2	45 x 16	14	165	48	22	6	
011036	Lead block 3 sheaved	600	1200	3	45 x 16	14	220	48	22	6	
011037	Lead block 4 sheaved	600	1200	4	45 x 16	14	275	48	22	6	
011038	Lead block 5 sheaved	600	1200	5	45 x 16	14	330	48	22	6	
011039	Lead block 6 sheaved	600	1200	6	45 x 16	14	385	48	22	6	